

PRODUCT

PAVISTAMP ASPHALT

Cold mix asphalt

- Repair of pothole and subsidence
- For quickly repair
- Used in all weather
- Ready for use

PRESENTATION /

Plastic bags of 25 kg.
Pallets of 1000 kg (40 bags).

COLORS /

Black.
Red (brick).

YIELD /

30 kg/sqm and 2 cm of thickness.

STORAGE /

12 months since the date of manufacture in closed original packaging and sheltered from the weather and sun.

DESCRIPTION /

Cold mix based aggregates of sand, limestone and bituminous binder

CHARACTERISTICS /

- Asphalt for repair and maintenance of highways, streets and roads...
- Adheres to all type of coatings
- Used in all climatic conditions.
- Allows immediately distribution.
- Long longevity.

HOW TO USE /

- **Pavistamp Asphalt:** does not require special preparation not even varnish for easy grip.



Cleaning and sweeping the area to be treated with a light thickening.
Minimum thickness: 2 cm
Maximum thickness: 6 cm



Flatten with a drop hammer manual or mechanically.



After flatten the asphalt spread a fine coat of sand.

COMPARED WITH OTHER ASPHALTS /

TYPE	NORMAL ASPHALT Aqueous emulsion binder	PAVISTAMP ASPHALT Bitumen: without water
ASPHALTING	+ o-	Excellent
CONCRETE	+ o-	Excellent
HIGH TEMPERATURE	YES	YES
RAIN	NO	YES
ICE	NO	YES
ADHESIVE LAYER	YES	NO
WATER HOLE	NO	YES
STORAGE	6 months	minimum 1 year

FEATURES /

- Physical state: strong
- Density: 1400-1800 kg/m³ to 20°C
- Solubility in water: insoluble to 20°C
- Explosion: not applicable
- Danger cautions: none