

PRODUCT**BRYTEN-CH****Surface retarder
for fresh concrete**

- On surfaces of concrete fresh exposed to the weather.
- Facilitates junction between the fresh concrete and the road layer **Pavistamp, Padec, Padec Industrial...**
- Aids to control the quick evaporation of moisture in surfaces of fresh concrete.

**PRESENTATION /**

Can of 25 litres
Palets 450 litres (18 cans)

COLOR /

Opaque white

YIELD /

0.300-0.500 L/SQM

ASPECT /

Liquid

CONSERVATION /

12 months since date of manufacture, in original closed
Packaged and shelter from weather.

***No special requirements on the use of this product.**

**DESCRIPTION /**

Wax emulsion aqueous base and control of damp.

CARACTERISTIQUES /

- Sur les surfaces de béton frais exposées au soleil.
- Sur les pistes d'aviation.
- Dalles en béton, canaux,...
- Facilite l'entretien du béton, avec des avantages concluants sur la résistance du trafic mécanique.
- Evite les fissuration superficielles.

DOSAGE /

- Relation of mix, 1 to 5
- 1 part of Brythen CH 5 parts of water

*DOSAGE RECOMMENDED FOR TEMPERATURES
BETWEEN 30-35 °C

INSTRUCTIONS /

- Apply by spray trying to form a uniform layer.
- The application must be realised when on the surface of the fresh by placed concrete bleed water disappears and taking a matte colour.
- The time of application of the product after the pouring of concrete will be approximately 45-60 minutes depending on ambient temperature.

FEATURES /

- Nature: paraffins and waxes
- Density: 0.95 g/cc
- PH: 6-7