

PRODUIT

FILMAT - R

Retardant liquid

- For concrete and mortars in warm weather.
- For transportation of prolonged concrete.
- Exempt of chlorides
- Easy application.



PRESENTACIÓN /

Bidón de 20 kg
Palets de 480 kgs (24 bidones)

COLOR /

Incoloro

RENDIMIENTO /

*Hormigones: 0.2-0.5%
sobre el peso del cemento
*Morteros: 15 gramos por saco de 25 kg

TEMPERATURA EXTERIOR /

A partir de 25-30°C

CONSERVACIÓN/

20-25°C, 12 meses a partir de la fecha de fabricación
en envase original cerrado y al abrigo de la intemperie
y humedad.



DESCRIPTION /

Retardant liquid for concretes and mortars.

APPLICATIONS /

- To increase the working time of concrete and mortar, when conditions require it.
- Controlling big volumes of concrete or mortar.
- In pumping and vibrated operations
- Lengthen time of start of setting in several hours.
- Reduce the traction of the mortar and concrete
- Do not produce air occlusion.

HOW TO USE /

- The dosage will vary between 0.2 – 0.5% on the weight of cement according to the characteristics of the concrete or mortar, as well as room temperature.
- Can be dissolved in water mixing.
- Realise tests before determine the proper dosage for each type of concrete and mortar.
- Use throughout the implementation process of dumping or the same dosage.

FEATURES /

- Aspect: Liquid
- Density: 1,05 g/cc
- Fire behavior: flammable

*All the information described has obtained from tests realized in Standard conditions and can vary according condition of placement.

