

COMPLEMENTARY PRODUCTS

PRODUCT

HORMIDUR - 100

Accelerant of setting for mortars

- For mortars and non-armed concretes.
- Based on chlorides.
- Improve the setting in cold time.
- Special for mortars monocoat.
- For fast form removal
- Easy utilization.



PRESENTATION /

Plastic Can of 28 kg
Palets of 672 kg (24 cans)

COLORS /

Colorless

YIELD /

Monocoat mortar: 0.150 l. by bag of 25 kg
Concretes: 3-5 % on the weight of cement
Outdoor temperature 5-10°C approx.

STORAGE /

12 Months in original closed container and shelter from the weather and moisture

*These results can vary according conditions of placement.

*For mortars and reinforced concretes and prestressed use **Hormidur SC**.



DESCRIPTION /

Liquid accelerant for the setting and hardening of the mortars and concretes.

APPLICATIONS /

- Accelerant that in cold environments (5-10°C) it allows reducing the waiting before the scraping of the mortar monocoat.
- When you don't want to decrease the production in seasons of winter temperatures.
- Like protection of the concrete to low temperatures.

SUPPORTS /

The habituals for the application of mortars and concretes.

RECOMMENDATIONS OF APPLICATION /

- Not applying a monocoat mortar in a frozen support or at risk of freezing.
- Not surpassing the recommended dosage, it could alter the features of the mortar.
- In mortars and concrete use always the same dosage.
- In monocoats of dark tones using always the same percentage, otherwise may cause discoloration.

HOW TO USE - DOSAGE /

- Dosage will vary between 3-5% on the weight of cement, according to the characteristics of concrete or mortar, the room temperature or product, as well as the speed of setting desired.
- It can be dissolved prior to mixing water, but you should always realize tests before to determine the best dosing

FEATURES /

- Nature: organic salts
- Aspect: transparent liquid
- Density: 1.3 DIN 51757
- PH: 7 UNE EN 1262
- Solubility in water: Total



www.pavistamp.com

Customer Service: +34 902 158 743