

**PRODUCT****HORMIDUR - SC****Accelerant of setting for concrete and mortars**

- Improve the setting in cold time
- For fast form removals
- Easy utilization
- Increase productivity

**PRESENTATION /**

Plastic can of 28 kg.  
Palets of 672 kg (24 cans)

**COLORS /**

Colorless.

**YIELD /**

Monocoat mortar: 0.150 l. by bag of 25 kg  
Concrete: 2-4 % on the weight of cement  
\*Exterior Temperature 5- 10°C approx.

**STORAGE /**

12 months in original closed container and shelter from weather and moisture.

**DESCRIPTION /**

Liquid accelerant without chlorides for mortar and concrete.

**APLICATIONS /**

- For concretes, prestressed and mortar even if they are armed.
- Totally exempt of chlorides
- When you refuse to decrease the production in winter time.
- Like protection of the concrete to low temperatures.

**SUPPORTS /**

The habitual for the application of mortars and concretes.

**RECOMMENDATIONS OF APLICATION /**

- How lower is the temperature and higher the relation water/cement for the same Speed setting, the dosage of **Hormidur SC** should be higher.
- Do not apply a concrete or mortar on a support frozen or at risk of freezing.
- Used throughout the implementation process of dumping or the same dosage.

**HOW TO USE- DOSIFICATION /**

- The dosage will vary between 2-4% on the weight of cement, according to the characteristics of concrete or mortar, the room temperature or product, as well as the Speedy of setting desired.
- Can be dissolving before with water of mixing, but is convenient always to realize previous tests to determine the best dosage.

**FEATURES /**

- Nature: organic salts
- Aspect: Liquid
- Density: 1.3 gr/ec
- PH: 7-7.75
- Chlorides: Totally exempt

\*These results can vary according to the conditions of placement.