

COMPLEMENTARY PRODUCTS

PRODUCT

LATEX MULTIUSO

Multipurpose resin

- Increased the mechanical strength
- Dirt repellent
- Improves the adhesion of mortars and paints

PRESENTATION /

Can of 20 litres
Palets of 480 litres (24 cans)

COLOR /

White (Finish dry transparent)

YIELD /

0.150- 0.200 lts./sqm once diluted

TO MIX MORTARS /

1.5 to 2 Lts. By bag of 25 kg

STORAGE/

12 months since manufacture date in original closed container and shelter from weather and moisture



COMMENTS /

- Application temperature: 5-30°C
- Do not apply on surfaces of concrete or disperse mortar.
- Do not apply on humid or wet supports.
- Avoiding the contact with the skin and using gloves and protective glasses.
- Do not contain aggressive elements.

DESCRIPTION /

Latex dispersed in water and organic and inorganic additives.

APPLICATIONS /

- Additive for traditional mortars in cementitious base, plaster, lime...
- Improves the adhesion of adhesive cement, monolayer, leveling paste.
- Supplementation of plastic paints, tempera...
- Paintable and washable.
- Exterior and interiors.

APPLICATION RECOMMENDATIONS /

- Application temperature: 5-30°C
- It can be used in time pass to the conservation and maintenance of any coating of mortar or concrete...

INSTRUCTIONS /

A) Dissolution 1 to 4

- Dilute 1 part of **latex multiuse** by 4 parts of clean water, in finishes of interiors and exterior son monocoat mortar, paint, natural stone...
- Application without overload 1 or 2 coats as traditional paint.

B) In addition and reinforcement of mortars recommend to dilute 50% with clean water.

FEATURES /

- Density: 2.1 g/cm³
- PH: 4.0
- Color: milk white

*All the information described has obtained from tests realized in Standard conditions and can vary according condition of placement.



www.pavistamp.com

Customer Service: +34 902 158 743