



#### **APPLICATIONS /**

- Synthetic mineral coating of high features to decoration for all kind of façades in exterior and interiors.
- New work, or rehabilitation
- Water and dirtines repellent
- Antimoho- antiverdin
- In walls and roofs
- Compatible with the majority supports

#### **ADMITTED SUPPORTS /**

- **Revex Plus**, concrete, monolayer mortar **Revistamp**, wood and plaster...
- On painted supports or old coatings, in restoration and in good conditions and perfectly adhered to the support.

#### **APPLICATION RECOMMENDATIONS /**

- Application temperature between 5 and 30°C.
- Do not apply with sun directly, rain or risk or freezing.
- Use tape adhesive for work joint.
- Protect all the areas that can be splash of the product, like Windows, floors...

## **High performance acrylic mortar**

### **MORTECRIL**

#### **DESCRIPTION /**

Mortar based of acrylic resins, charges, pigments minerals and additives organic and inorganic.

#### **COMMENTS /**

- Do not apply on horizontal or inclined surfaces at less than 45°.
- Protect the top edge of the coating from the water rain penetration.
- Do not add any additive to the mortar.

#### **USE CHARACTERISTICS /**

- Application thickness of 2 to 3 mm by layer.
- Troweling time: 20-30 min. Approx. Depending on weather conditions.
- Hard to the touch: 6-7 hours
- Hardening total time: 16-17 hours

\*These times may vary considerably depending on room temperature

#### **FEATURES /**

- Paste density: 1905 kg/m<sup>3</sup>
- Dry retraction: 4.50 mm/m
- Capillary water absorption: 0.04 kg (m<sup>2</sup> . min 0.5)
- Adherence: 2.00 N/mm<sup>2</sup>
- Fire behaviour: non combustible

\*Test acccording to Stanadard CE UNE- EN1015.

\*These results may vary depending on conditions of placing.



**MORTAR  
MORTECRIL  
ACRYLIC**

**EXECUTION CONDITIONS /**

- The support must be flat, clean up, stable and resistant, free of dust, loose particles, remnants of ancient paintings, oils ...
- On very absorbent or highly dispersed, before applying a primer coat **F-300** diluted with water (1 part F-300, 3 parts water).

**HOW TO USE /**

The product supplies ready for use, you can add till 1 litre of water per can and remove the content until total homogenization of the paste.



Apply **Mortecril** with gun of projection until obtain a finish like stucco or plain with plastic spatula.



Finish towelled:  
Extend the product with the trowel until obtain the right consistency.



Use masking tape to perform the job boards or any imitation of brick, stone...

**PRODUCT**

**MORTECRIL**

**High performance acrylic mortar**

- Finished plastering – stucco
- Excellent adhesion
- Anti-mildew-anti-moss
- Resistant to aging
- Washable
- Range of colors

**PRESENTATION /**

Cans of 25 kg.  
Pallets of 600 kg (24 cans)



**COLORS /**  
Chart of 24 colors

**YIELD /**  
2-3 kg/m2 and mm of thickness

**STORAGE /**  
12 months since date manufacture in original closed container and shelter from weather and moisture

**RANGE COLORS/**

