

PRODUCT

**ORFAPOL 50
(2 components)**

Based water polyurethane resin

- Excellent adhesion in different surfaces
- Enhance the color
- High resistance to abrasion
- Indoor and outdoor

PRESENTATION /

Cans of 5.5 and 11 kg.
Components A and B



COLORS /

Transparent

YIELD /

0.100 kg/m² (5 kg = 50m²) according to supports

ASPECT /

Satin – Matt

STORAGE /

12 months since date manufacture in closed original container and shelter form weather and moisture.

FEATURES/

Density: 1,00 – 1,05 g/ml 25°C

Flashpoint: not applicable

Recommended thinner: Water



DESCRIPTION /

Polyurethane resin two components water based, polyisocyanates with polymers, solvents and additives.

APPLICATIONS /

- Curing water based, to protect floors and walls.
- Transparent, waterproof and breathable.
- Excellent color enhancer.
- No staining.
- It helps low retention of dirtiness.
- Indoor and outdoor.

USE CHARATCERISITICS /

- The surface to treat will be clean and completely dry.
- With roller or brush.
- Sand the surface to promote adhesion.
- Pouring the components A and B in the same container and mix carefully with shaker.
- Let stand during 10 minutes.
- Apply in 2 coats without overload, waiting at least 45-60 minutes between coats.
- Avoid the layer is too thick, because it may delay the development of the final product (deeply dry and water resistant).
- It can be diluted between 5 and 25% with water.

HOW TO USE /

- The surface must be completely clean, dry and free of dust, grease...
- Proportion of mix in parts:
 - o 10 parts Component A
 - o 1 part Component B
- Pot life 2 hours.
- Open time 40-50 minutes.
- Minimum dry time 2 hours, max 24 hours.
- Application conditions: 10°C and 30°C UR <80%.

* These results are from tests standard and may vary depending on the conditions of placing.

