

POINTING OF CERAMIC



APPLICATIONS /

- Colored mortar to fill joints between tiles of 3 to 15 mm, in any kind of pavement or ceramic coating **Revistamp E**.
- Mortar for application in paste.
- Indoor and outdoor.
- Radiant heating floors.
- In joints higher than 15 mm, the paste will be more consistency.

APPLICATION RECOMMENDATIONS /

- Application temperature 5°C to 30°C
- The mixing will be equal to the consistence of concrete color.
- Respect always the same proportion of water, the excess of water will difficult the cleaning, as well as the finishing touch.
- Do not apply as grout.
- Avoid applying in rainy or damp weather with risk of freeze or hot weather.

Colored mortar for wide joint of 3 to 15 mm.

PAVICOLOR - JG (wide joint)

DESCRIPTION /

Cement, selected aggregates, synthetic resins, organic additives and inorganic mineral pigments.

COMMENTS /

- Controlled retraction and fungicide.
- For joints less than 3 mm use **Pavicolor-JF**.
- In deformable supports, use **Pavicolor-F**.
- In façades use **Pavicolor-F**.

USE CHARACTERISTICS /

- Rest time after mixing: 5 minutes
- Maximum time for cleaning: 30-60 minutes
- Mass life: 60 minutes
- Put into service: 3-4 days

*These times can vary considerably depending on temperature.

FEATURES /

- Apparent powder density: 1.4 g/cm³
- Mixing water: 25%
- Mass density: 1.8 g/m³
- Capillary: 0,5 g/dm³

*These results has been obtained in standard conditions and may vary depending on conditions of placement



PONTING OF CERAMIC
PAVICOLOR JG
 WIDE JOINT

EXECUTION CONDITIONS /

- The joints between ceramic will be clean, dry and free of dust.
- The pointing should be realized 24 – 48 hours after fixation of the ceramic.

In applications on porous or absorbent surfaces, realize a treatment of tiles with **Protector PAVISTAMP**, before realize the pointing to prevent stained the pieces.

PRODUCT

PAVICOLOR - JG (wide joint)

Colored flexible mortar for wide joint of 3 to 15 mm

- Excellent workability
- Without cracking
- Water resistant
- Is supported color mixture

HOW TO USE /



Mix **Pavicolor JG** with 1.3 litres of clean water per bag of 5 kg with low speed mixer until obtain homogeneous mass.

*Let rest 5 minutes



Fill up the joints between tiles. Wait 30-60 minutes to eliminate the product remains.

Clean with a wet sponge and rinse with clean water until get the desired finishing touch (cleaning should be done with the hardened product, 12-24 hours depending on room temperature)

*Can apply with gun refillable.

PRESENTATION/

Bag of 5kg (in boxes of 20 kg)

Pallets of 18 Boxes (360 kg)

*Bags of 25 kg (on request)

COLORS /

12 colors

*Others on request

YIELD /

Between 0.4 and 0.8 kg/m²

*These consumption may vary depending on thickness and length of joints, as well as dimension of ceramic material.

STORAGE /

12 months since date manufacture in original closed container and shelter form weather.

