

PRODUCT**PROTECT FACHADAS - S****Waterproofing**

- Pearl effect.
- Repellent to the penetration of rain water.

**PRESENTATION /**

Containers of 20 kg
Palet of 432 kgs (24 containers)

COLOR /

Yellowish

YIELD /

Recommendable: 1 kg by 3 sqm in one coat

CONSERVATION/

20-25°C, 12 months since manufacture date in original closed container and shelter from weather and moisture.

**DESCRIPTION /**

Waterproofing ready for use, silicone base.

APPLICATIONS /

- Excellent penetration.
- Specially formulated for quick drying on all surfaces appears neutral or alkaline water-repellent effect in the hours after its implementation.
- Breathable

INSTRUCTIONS

- The support must be dry, clean and free from dust.
- Only on vertical support.
- After the rain, wait at least 24 hours before apply.
- In surfaces recently worked, wait at least 30 days before start the treatment.
- Applied by brush in rough materials or with roller, or spray.
- In general, only one coat is enough, in case of very porous surfaces, a second coat is necessary just disappear the bright effect of the first coat.

FEATURES /

- Active materia: approx. 6%
- Density 25°C: 0.85 g/cm³

*All the information above has been obtained from tests performed under Standard conditions and may vary depending on the conditions of placement.

OBSERVATIONS /

- Avoid splashing in eyes and contact skin.
- Use safety glasses and gloves.
- Contains solvents.