

**PRODUCT****RACLY 2 - COLOR****Sealed thermoplastic, waterproofing and colored resin**

- To colored concrete pavements
- Suitable to maintenance
- Resistant to freeze and thaw

**PRESENTATION /**

Cans 20 litres  
Palets of 480 litres (24 cans)

**COLORS /**

Colors on request

**YIELD /**

150-200 g/sqm and coat

**ASPECT /**

Semi-bright

**STORAGE /**

12 months since manufacture date, in original closed container, and shelter from weather and moisture.

**FEATURES /**

Solid matter: 60 ± 2  
Color index: ≤ 2  
Viscosity: 6000 – 12000 cps.

**DESCRIPTION /**

Acrylic copolymer colored for treatment and protection of concrete pavement and road signs.

**FEATURES /**

- Acrylic thermoplastic emulsion with dry process purely physical.
- Its principal field is sealed and coating of colored concrete pavements.
- Plain concrete or printed
- To enhance floor colors

**RECOMENDATIONS OF USE /**

- Once the pavement is completely dry (approx. 24 hours according room temperature) applies **Racly 2 Color** with roller or airless (recommended two coats).
- Supplied ready for use.
- Do not add any additive to the resin.
- Indoor good ventilation applies.
- During application use gloves, mask and safety glasses.
- Do not apply with risk of rain or freezing, moisture or strong hot.
- Application temperature between 10-25°C
- Can be used passing of time to conservation and maintenance of any concrete floor plain, decorate or stamped.

**INSTRUCTIONS /**

- The pavement must be completely dry and free of dust, oils,...
- Application without surcharge in two coats.
- Hard to the touch 2 hours.
- Passable 24 hours.
- Road traffic 48 hours.

\*These results can vary according conditions of placement.

