

PAVEMENTS FLOOR RENOVATION

PRODUCT

RACLY 2

Thermoplastic resin and waterproof sealing

- Concrete pavement curing
- Highlight color
- Suitable for maintenance
- Freeze-thaw resistance



PRESENTATION /

Can of 20 litres
Pallets of 480 litres (24 cans)

COLORS /

Colorless

YIELD /

150-200 g/m² and coat

ASPECT /

Semi-gloss

STORAGE /

12 months since date manufacture, in closed original container and shelter from weather and moisture.

REFERENCES/ Color resin **Racly 2 Color**



DESCRIPTION /

Acrylic copolymer solution for treatment and protection of concrete pavements and road signs.

CHARACTERISTICS /

- Thermoplastic acrylic emulsion with a purely physical process of drying.
- Its main field of application is the sealing and coating of concrete pavements.
- Printed or plain concrete.
- To highlight color in floors.

APPLICATION RECOMMENDATIONS /

- Once the floor is completely dry (summer ≥ 10 days/ winter ≥ 28 days) applies **Racly 2** with roller or airless spray (recommended 2 coats).
- Supplied ready to use.
- Do not add any additives to the resin.
- Indoor applied with good ventilation.
- During the application use gloves, mask and safety glasses.
- Do not apply with risk of rain or freezing, moisture or intense heat.
- Application temperature between 10-25°C (measured on the pavement)
- Can be used over time to the preservation and maintenance of any concrete floor plain, decorated or printed.

HOW TO USE /

- The pavement will be completely dry and free of dust.
- Application without overload two hands.
- Hard to the touch 2 hours.
- Walked on 24 hours.
- Road traffic ≥ 48 hours.

*These results may vary depending on the conditions of placing.

FEATURES /

Solids: 60 \pm 2
Color index: ≤ 2
Viscosity: 6000 – 12000 cps.