

PRODUCT**TINTE****Waterproof
enhances color**

- Excellent adhesion to the mortar
- Enhances color
- Good resistance to weathering
- Satin finish

**PRESENTATION /**

Container of 8 kg

COLORS /

9 colors standar

*Others on request

**YIELD /**

150-200 g/m² (once reduced)

APPEARANCE /

Satin

STORAGE /

2 years in original closed container and shelter from weather and moisture.

FEATURES /

Non-volatile Material: 13%

Viscosity: 4140 cPs

P.H.: 7.5

Work Temperature: 10- 30 °C

DESCRIPTION /

Low consistency paste, made by active, solubilized in organic solvent.

FEATURES /

- Grease dye.
- Waterproof and breathable.
- Enhance the color.
- Helps to low retention of dirtiness.
- Indoor and outdoor.
- Chart of 9 colors.

APPLICATION RECOMMENDATIONS /

- The surface to treat should be completely dry and free of moisture.
- With sponge, spray gun or brush.
- Avoid too thick layer, this could deteriorate the final characteristics of the product.
- To enhance the different aspects of tonality or aged, sponging gently on the paste applied on fresh.
- On new mortar, this must be completely dry (≥ 28 days).
- Do not apply at risk of rain, freeze-thaw.

HOW TO USE /

- Mix 1 part of dye with 1 or 2 of White Spirit or Diluent universal.
- Pot life: 10 hours.
- Open time: 15-30 minutes.
- Time to dry: 2-5 hours.

*These results may vary depending on conditions of placing.

**ROJO****NEUTRO****AZUL*****NEGRO****PARDO****OCRE****SALMÓN****BLANCO****VERDE***

*Colors on request